



# National Auto Fleet Group

A Division of Chevrolet of Watsonville

490 Auto Center Drive, Watsonville, CA 95076

(855) 289-6572 • (855) BUY-NJPA • (831) 480-8497 Fax

Fleet@NationalAutoFleetGroup.com

04/18/2018

Quote ID 6587

Mr. Dominc Machi

Mount Diablo Unified School District  
1936 Carlota Drive  
Concord, CA 94519

Dear Mr. Machi,

National Auto Fleet Group is pleased to quote the following vehicle(s) for your consideration.  
**Three (3) New/Unused (2019 Peterbilt 337 Chassis with 24' Refrigerated Reefer Box)**  
Provided by Mr. Lopez with Coast Counties Peterbilt each for:

	One Unit (1)	Extended Units (3)
Sub Total	\$ 139,038.00	\$ 417,114.00
Tax (8.75%)	\$ 12,165.83	\$ 36,497.49
Total	\$ 151,203.83	\$ 453,611.49

This vehicle(s) is available under the **National Joint Powers Alliance Contract 081716-NAF**.  
Please reference this Bid Number on all Purchase Orders.

Thank you in advance for your consideration. Should you have any questions, please do not hesitate to call.

Sincerely,

Jesse Cooper  
National Fleet Manager  
[jcooper@Nationalautofleetgroup.com](mailto:jcooper@Nationalautofleetgroup.com)  
Office (855) 289-6572  
Fax (831) 480-8497





**Marathon Industries, Inc.**  
 P.O. Box 800279 Santa Clarita 91380  
 1-(661) 286-1520 Fax: 1-(661) 286-1533  
*Dedicated to serving you better!*  
**WWW.MARATHONTRUCKBODY.COM**

**SALES QUOTATION**

Sales Quote No	QT-045255
Sales Quote Date	04/12/18
Customer No.	COAC
Customer PO No	
Customer PO Date	04/12/18
Payment Terms	Net 30 days
Salesperson	Tom Garcia
Quoted By	Tom Garcia

Quote Expiration Date : 05/12/18

**Sold To:**  
 Coast Counties - San Leandro  
 Tim lopez  
 260 Dolittle Dr.  
 San Leandro, CA 94577

**Ship To:**  
 Coast Counties - San Leandro  
 260 Dolittle Dr.  
 San Leandro, CA 94577

Tel: 510-568-6933  
 Fax: 510-562-5564

Tel:  
 Fax:

**Year:**  
**Make:**  
**Model:**  
**Wheel Base:**  
**Cab to Axle**  
**Pool Chassis:** No  
**VIN Number:**  
**Serial Number:**  
**License No.:**

Item:

Item No.	Description	Unit	Qty Order
2REF249693	Mount Diablo USD 24'6"OLx102"OWx94"IH Reefer VB 23'8" IL x 94" IH x 102" OW Pre-painted Polar White .050 Aluminum Wall Panels Sprayed Foam insulation, Walls & Ceiling w/ 3" + Floor & Bulkhead w/ 4", Sprayed in place. Walls, Ceiling, and Bulkhead are lined w/KemPly w/Thermobreaks Aluminum Inverted T Floor w/12" Extruded Aluminum Kick Plate Cross members 12" on ctr - 9" Aft R. Axle Aluminum/Steel Contacts Protected w/Electrolytic Treatment Stainless Steel Rear Portal Reinforced Threshold has added Cross Member and Base Stiffeners Top of Portal Reinforced W/ Internal Gussets Front Bulkhead Reinforced Special 11 GA Frt C. Member W Extra Long Rails Fiberglass front radius panel for reefer mount One piece Aluminum Roof Aluminum Roof Bows bonded every 24" on Center (2) Interior Dome lights All LED Lights LED Marker and Tail - Lights meet MVSS #108 (Interior & BU Lights Conventional) 1 1/8" Insulated Overhead Roll-Up Rear Door Door Has Inside Emergency Release Mud flaps, Grab Handles, and Undercoating (2) Floor Drains at Front and Full Sub Pan Bulkhead is reinforced for Stand Alone reefer unit (Thermo Kinmg T-680 R-50 ) Front radius Service Steps & Grab Handle Inc.	Each	1
8VBOPT1017	Extra Width VB/HC 102" Wide	Each	1



**Marathon Industries, Inc.**  
 P.O. Box 800279 Santa Clarita 91380  
 1-(661) 286-1520 Fax: 1-(661) 286-1533  
*Dedicated to serving you better!*  
**WWW.MARATHONTRUCKBODY.COM**

**SALES QUOTATION**

Sales Quote No	QT-045255
Sales Quote Date	04/12/18
Customer No.	COAC
Customer PO No	
Customer PO Date	04/12/18
Payment Terms	Net 30 days
Salesperson	Tom Garcia
Quoted By	Tom Garcia

Quote Expiration Date : 05/12/18

**Sold To:**

Coast Counties - San Leandro  
 Tim Lopez  
 260 Dolittle Dr.  
 San Leandro, CA 94577

**Ship To:**

Coast Counties - San Leandro  
 260 Dolittle Dr.  
 San Leandro, CA 94577

Tel: 510-568-6933  
 Fax: 510-562-5564

Tel:  
 Fax:

**Year:**  
**Make:**  
**Model:**  
**Wheel Base:**  
**Cab to Axle:**  
**Pool Chassis:** No  
**VIN Number:**  
**Serial Number:**  
**License No.:**

Item:

Item No.	Description	Unit	Qty Order
	<i>Transferred from page 1.....</i>		
8WALL1003	E Track - non inlaid located @ 30" & 60" O/C	Foot	96
8LIFT1000	Maxon BMR-44 , 4400lb columnlift 84 x 86 steel platform 16" ARR Cab on/off swtich	Each	1
8OPT1025	Extra Battery Kit Dual Inc. Battery Box, 2 Group 31 Deep Cycle Batteries Solenoid & Wiring into chassis electrical system	Each	1
8OPT1026	Back Up Camera w/ Monitor	Each	1
8OPT1000	Safety Conspicuity reflective tape on sides & ICC	Each	48
8FREIGHT1010	One Way to No. Cal Bay Area	Each	1
8FREIGHT27	Weight Certificate & Misc Fuel	Each	1

Option: Thermo King T-680 R-50  
 Self contained reefer unit , deal direct  
 with Thermo King Add price of T-680  
 R-50 \$18,980.00

**Subtotal:** 30,865.00  
**Invoice Discount:** 0.00  
**Tax Amount:** 0.00  
**Total:** 30,865.00



**Marathon Industries, Inc.**  
 P.O. Box 800279 Santa Clarita 91380  
 1-(661) 286-1520 Fax: 1-(661) 286-1533  
*Dedicated to serving you better!*  
**WWW.MARATHONTRUCKBODY.COM**

**SALES QUOTATION**

Sales Quote No	QT-045255
Sales Quote Date	04/12/18
Customer No.	COAC
Customer PO No	
Customer PO Date	04/12/18
Payment Terms	Net 30 days
Salesperson	Tom Garcia
Quoted By	Tom Garcia

Quote Expiration Date : 05/12/18

**Sold To:**

Coast Counties - San Leandro  
 Tim Lopez  
 260 Dolittle Dr.  
 San Leandro, CA 94577

Tel: 510-568-6933  
 Fax: 510-562-5564

**Ship To:**

Coast Counties - San Leandro  
 260 Dolittle Dr.  
 San Leandro, CA 94577

Tel:  
 Fax:

Item:

**Year:**

**Make:**

**Model:**

**Wheel Base:**

**Cab to Axle**

**Pool Chassis:** No

**VIN Number:**

**Serial Number:**

**License No.:**

**ADDITIONAL TERMS AND CONDITIONS**

**1. Sales Quotation, Order, and Invoice.** The Sales Quotation, Sales Invoice, and Sales Order are intended to supplement each other and they constitute a binding Contract, jointly and severally, between Marathon Industries, Inc. ("Marathon") and the Customer referenced on the specified documents. Such documents incorporate these Additional Terms and Conditions which shall be deemed part of the Contract. In case of conflict between the documents, the Sales Invoice shall define and determine the terms of the Contract.

**2. Labor and Material.** The Customer shall pay all charges for labor and materials used on the work covered by the Contract within the payment terms of this Sales Invoice stated above. Any balance remaining unpaid payment terms shall accrue simple interest at the rate of 15% per annum until paid.

**3. Withdrawal of Quotation.** The Sales Quotation will be considered a proposal until a copy, signed by the Customer, has been delivered to Marathon's office. Until that time, Marathon has the right to withdraw the proposal by written notice delivered to the Customer or when quote expires.

**4. Extra Work.** The price set forth in this Contract shall be deemed to be full compensation for all work and materials furnished by Marathon as called for by the Contract, agreed upon within plans, or agreed upon written specifications. Additional compensation shall be paid to Marathon pursuant to written revised Sales Quotations signed by the Customer stating that the work is extra and designating the amount to be paid for the extra work.

**5. Delay.** Marathon shall be excused for any delay in completion of the work caused by acts of God, acts of the Customer, or the Customer's employees, agents, or representatives, inclement weather, labor troubles not the fault of Marathon, Customer requested extra work, failure of Customer to make payments when due, and other contingencies unforeseen by Marathon and beyond the reasonable control of Marathon.

**6. Attorney Fees.** In any legal action arising out of this Contract or the performance thereof, the court in such litigation, shall award reasonable attorneys fees to the prevailing party. Unless judgment is obtained by default, the attorneys fee award shall not be computed in accordance with any court schedule, but shall be in such amount as to fully reimburse all attorneys fees actually incurred in good faith, regardless of the size of the judgment, it being the intention of the parties to fully compensate for all attorneys fees paid or incurred in good faith.

**7. Venue.** Any legal action arising out of this Contract shall be filed in Los Angeles County, State of California, which is the exclusive venue for any such actions.

**8. Bankruptcy.** If the Customer should file a petition in bankruptcy or make an assignment for the benefit of creditors, Marathon shall be paid the reasonable value of all work performed under this Contract, and the obligations of all parties under this Contract shall thereupon terminate. In determining reasonable value under this paragraph, the Contract price shall be deemed to be reasonable.

**9. Notice.** Any notice required or permitted under this Contract may be given by ordinary mail at the address set forth in the Contract, but such address may be changed by written notice given by one party to the other from time to time. Notice shall be deemed received in the ordinary course of the mails.

**10. Liens.** Customer hereby grants to Marathon all general, possessory, and retaining liens, and all special or charging liens known to common law, for Marathon's unpaid fees, costs, and expenses, on any amount recovered in any action arising out of the Contract by settlement, arbitration award, judgment at trial, or otherwise. Customer understands and agrees that Marathon shall have the right to retain any personal property of Customer as security for any and all amounts owed to Marathon by Customer under this Contract and expressly agrees that Marathon may sell or otherwise dispose of such property after the giving of 30 days written notice as satisfaction, either in full or part, of any amounts owed to Marathon under the Contract.

**11. Severability and Amendment.** It is understood and agreed that should any provision of the Contract be found to be unenforceable, such unenforceable provision shall not affect the remaining portions or provisions of the Contract. The Contract may be amended only by a writing signed by all the parties, is binding on, and shall inure to the benefit of, the successors and assigns of the parties, and shall not be assignable except by written agreement between Marathon and Customer.

**12. Chassis breakdowns or mechanical malfunctions are the sole responsibility of the Customer.**

**Please Sign and Date to accept the terms and conditions of this quotation.**

Signed : \_\_\_\_\_

Purchase Order : \_\_\_\_\_ Date : \_\_\_\_\_

Pool Chassis [ ] or Customer Chassis [ ] or Est. Chassis Arv. [ ]

Chassis Model \_\_\_\_\_ Chassis Ready for Pick Up [ ]

VIN # \_\_\_\_\_

Special Delivery Instructions : \_\_\_\_\_

\_\_\_\_\_



Los Angeles - Fontana - San Diego - San Leandro - Sacramento - Stockton - Redding - Las Vegas - Reno  
 Phone: 800-211-8080 Fax: 323-582-5835

## T-680R 50 Advanced Reciprocating Compressor



Date: **4/13/2018**  
 Contact: **TIM LOPEZ**  
 Company: **COAST COUNTIES**  
 Address: **260 DOOLITTLE DR**  
**SAN LEANDRO**  
**CA 94577**

Salesperson: **VERNON PASSINI**  
 Proposal # **41318-T680R50**  
 Temperature application & specifications:  
**MT DIABLO SCHOOL DISTRICT**

Electric motor required: Voltage 230/3p

**System application:**

Ambient Temp.	95	°F	Box size:	24'
Set point Temp.	32	°F	Rear/Side door type:	rollup
Product type:	freh		Insulation thickness:	3x3x3x4
Running hours daily:	8		Rear/Door openings	0 Per day
Deliveries / day:	10		Side/Door openings	0 Per day

**STANDARD FEATURES:**

SMART REEFER microprocessor controller	Cycle-Sentry start/stop control system
Auto Phase Correction	Diesel/electric auto-switching
Warranty 2 yr. Major Components/1 yr. Basic	TherMax system
EMI 2000 extended maintenance	Silicone coolant hoses

**REFRIGERATION CAPACITY:**

Return Air to Evaporator	35 Degrees F	0 Degrees F	-20 Degrees F
<b>With Standard R-404A Refrigerant Package</b>		BTU/hr. (Up to)	
Capacity on engine power	18,000	11,000	7,000

**AIRFLOW: on high speed engine operation**

Airflow Volume @ 0 Pa static pressure	1600		ft <sup>3</sup> /min
Discharge Velocity (air flow)	18		ft./sec

**DIESEL ENGINE: 3 Cylinder, Liquid Cooled**

Model	TK 370
Rating	12 hp
Maintenance Interval	2000 hrs.

**ELECTRIC STAND-BY MOTOR**

Voltage / Phase / Cycles	230/3/60
--------------------------	----------

**WEIGHT:**

Complete System	1018
-----------------	------

**DIMENSIONS: inches**

	<b>Height</b>	<b>Width</b>	<b>Depth</b>
Condenser	24	74	13
Evaporator	13	36	13

You are a special customer and your business is greatly appreciated. Many thanks!

**PRICING:**

Refrigeration system price: \$ 18,980.00 /Each  
Option: System installation *Included*  
\*Option: 2nd Year extended warranty, full coverage, 4000 hours, \$0.00 deductible. *NOT Included*  
Option: Electric standby 230 v/3p/60Hz *Included*  
Option: Standard Control Display *Included*

**TOTAL PRICE PER SYSTEM:**

\$ 18,980.00 F.O.B.: TK Services / San Leandro  
Applicable Taxes are not included

**TK SERVICES, INC. TERM & CONDITIONS**

- \* All above prices are firm for 30 days, terms are C.O.D.
- \* We are unable to accept credit card payments.
- \* We accept CASHIER CHECK PAYMENTS for C.O.D. accounts
- \* In those cases where the OEM cannot supply the equipment on the promised date, you will be invoiced a maximum of 7 days from the date of installation

**CUSTOMER ACCEPTANCE TO UNIT, OPTIONS, PRICE, TERM & CONDITIONS:**

TK Services, Inc. Thanks You  
for your confidence in our products.

Please sign below and return to

Sincerely,

*Vernon Passini*  
\_\_\_\_\_  
VERNON PASSINI

PO # \_\_\_\_\_  
VIN # \_\_\_\_\_  
STOCK # \_\_\_\_\_  
Signature: \_\_\_\_\_  
Title: \_\_\_\_\_  
Date: \_\_\_\_\_  
Body Builder: \_\_\_\_\_  
Approx. Date Truck to Arrive to T.K. \_\_\_\_\_

**\*\* IMPORTANT \*\***

TEMPERATURE APPLICATIONS, MODEL SPECIFICATIONS AND TECHNICAL OPTIONS OF THERMO KING REFRIGERATION SYSTEMS, MUST BE CONFIRMED AND APPROVED BY A THERMO KING SALES CERTIFIED ACCOUNT EXECUTIVE AND MEET THERMO KING CORPORATION'S EQUIPMENT RATING. FAILURE TO MEET THIS CONDITION WILL VOID WARRANTY.

Reference: 0 COAST COUNTIES

**WARRANTY REGISTRATION**

*Please complete this form when quoting or purchasing a Thermo King refrigeration system unit from TK Services, Inc.  
This information is required by Thermo King Corporation.*

<b>Thermo King Model:</b> _____	<b>Unit Serial Number</b> _____	<b>Date in Service</b> _____
<b>Company Name / User</b> _____	<b>Address</b> _____	<b>City / State</b> _____
<b>Zip Code</b> _____	<b>Phone #</b> ( ) _____	<b>E-mail</b> _____

*Terms of the Thermo King Warranty are available on request.*

**PLEASE INCLUDE THE COMPLETED FORM WITH YOUR SIGNED ORDER  
THANK YOU! TK SERVICES, INC.**



Coast Counties Peterbilt C501  
260 Doolittle Drive

Nat Auto Fleet GP/ MDUSD  
1936 carlota dr

San Leandro, California United States 95477  
Phone:  
Fax:  
Email: [tlopez@coastcounties.com](mailto:tlopez@coastcounties.com)

concord, California United States 94519  
Phone: (925) 682-8000  
Fax:  
Contact Email:  
Prepared for: **dominc machi**

### Vehicle Summary

	Unit		Chassis	
Model:		Model 337	Fr Axle Load (lbs):	10000
Type:		Full Truck	Rr Axle Load (lbs)	20000
Description:		24' Reefer	G.C.W. (lbs):	26000
	<b>Application</b>		Road Conditions:	
Intended Serv.:	Refrigerated Freight		Class A (Highway)	100
Commodity:	Other Commodity		Class B (Hwy/Mtn)	0
	<b>Body</b>		Class C (Off-Hwy)	0
Type:	Van		Class D (Off-Road)	0
Length (ft):	24		Maximum Grade:	6
Height (ft):	13.5		Wheelbase (in):	256
Max Laden Weight (lbs):	8000		Overhang (in):	99.70001
	<b>Trailer</b>		Fr Axle to BOC (in):	69.8
No. of Trailer Axles:	0		Cab to Axle (in):	186.2
Type:			Cab to EOF (in):	285.9
Length (ft):	0		Overall Comb. Length (in):	393
Height (ft):	0.0			
Kingpin Inset (in):	0		<b>Special Req.</b>	
Corner Radius (in):	0		California Registry	
	<b>Restrictions</b>			
Length (ft):	40			
Width (in):	102			
Height (ft):	13.5			

Approved by: \_\_\_\_\_

Date: \_\_\_\_\_

**Note: All sales are F.O.B. designated plant of manufacture.**

	Ask your dealer for a quote today, or visit our website @ <a href="http://www.paccarfinancial.com">www.paccarfinancial.com</a> .
	PACCAR Financial offers innovative finance, lease and insurance programs customized to meet your needs.

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	4/18/2018 10:34:35 AM	<b>Complete</b>	Model Number:	Model 337
Effective Date:	Jan 1, 2018		Quote/DTPO/CO:	Q83350335
Prepared by:	Tim Lopez		Version Number:	36.21



Coast Counties Peterbilt C501  
260 Doolittle Drive

Nat Auto Fleet GP/ MDUSD  
1936 carlota dr

San Leandro, California United States 95477  
Phone:  
Fax:  
Email: [tlopez@coastcounties.com](mailto:tlopez@coastcounties.com)

concord, California United States 94519  
Phone: (925) 682-8000  
Fax:  
Contact Email:  
Prepared for: **dominc machi**

	Description	Weight
<b>Base Model</b>		
	<b>Model 337</b> The Peterbilt Model 337 is built to take on the big jobs. That's why it's available as a Class 7 truck or tractor with a GVW up to 33,000 lbs. With a full range of suspensions and in an all-wheel-drive configuration, the 337 delivers an ideal match for applications such as wrecker, tanker, beverage delivery, municipal utilities – just about any job you can throw at it.	10,070
	<b>Other Commodity</b>	0
	<b>Refrigerated Freight</b> Truck or tractor used in over-the-road hauling of refrigerated freight. Pickup to delivery distance is typically over 100 miles and annual mileage is typically over 60,000 miles per year. Operation is typically on-highway.	0
	<b>Van</b>	0
	<b>California Registry</b> Required for all vehicles that will be registered in the State of California.	0
<b>Configuration</b>		
	<b>Not Applicable</b> Secondary Manufacturer	0
	<b>Class 6 Chassis Weight Rating 26,000 lb GVWR</b> Hydraulic Brake Chassis requires 8,000/10,000 lb Front Axle and can not exceed 20,000 lb Rear Axle (Rear Axle will be derated to a maximum of 18,000 lb). Air Brake Chassis requires 10,000 lb Front Axle and can not exceed 21,000 lb Rear Axle. Contact your Local State Agency regarding any special licensing requirements for Air Brake Chassis.	0
<b>Frame &amp; Equipment</b>		
	<b>10-5/8in Steel Rails 385-444in</b> 10.625 x 3.45 x .313 Dimension, 1,776,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 14.8 cubic inches. Weight: 1.44 lbs/inch pair	449
	<b>256in Wheelbase</b>	0
	<b>Custom Wheelbase or Overhang</b> Engineering approval may be required.	0
	<b>Three-Piece Crossmembers</b>	0
	<b>EOF Square without Xmbr</b> For use with body builder installed crossmember.	0

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	4/18/2018 10:34:35 AM	<b>Complete</b>	Model Number:	Model 337
Effective Date:	Jan 1, 2018		Quote/DTPO/CO:	Q83350335
Prepared by:	Tim Lopez		Version Number:	36.21





Description	Weight
<b>Omit Rear Mudflaps and Hangers</b>	0
<b>Front Axle &amp; Equipment</b>	
<b>Dana Spicer D1001IL 10,000 lb, 3.5 in. Drop</b>	23
Axle features an integrated air disc brake (IADB) knuckle to improve braking and reduce maintenance for IADB applications. The axles are designed for applications with a gross axle weight rating (GAWR) from 10,000 to 14,600 pounds. IADB feature eliminates separate torque plate and fasteners. One piece forged design includes tie rod arm, torque plate and spindle. The forged knuckle adds reliability for turn angles and the unique design features improved durability and camber alignment.	
<b>Taper Leaf Springs, Shocks 10,000 lb</b>	0
<b>Power Steering Sheppard HD94</b>	0
For use with 10,000 to 13,200 lb. axle ratings.	
<b>Power Steering Reservoir Frame Mounted</b>	0
<b>PHP10 Iron PreSet Hubs-Air Disc</b>	0
<b>Dana Spicer Wide Track IPO Std, Front Axle</b>	5
71in KPI IPO 69in for E1202, E1322, E1462, D2000F front axles. For improved turning radius.	
<b>Air Disc Front Brakes</b>	0
Complies with reduced stopping distance regulations.	
<b>Rear Axle &amp; Equipment</b>	
<b>Dana Spicer S21-170 21,000 lb</b>	211
Laser factory axle alignment to improve handling & reduce tire wear. Magnetic rear axle oil drain plug captures & holds any metal fragments in drive axle lube to extend service life. Parking brakes on all drive axles for optimal performance. Cognis EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life.	
<b>PHP10 Aluminum PreSet Hubs</b>	0
<b>Standard Stroke Parking Brakes</b>	0
Drive Axle(s). Not for use on U.S. or Canada Tractors, other than Car Carriers.	
<b>Gusseted Cam Brackets, Drive Axle(s)</b>	2
<b>SBM Valve</b>	0
Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.	
<b>Upsize Parking Brakes</b>	0
<b>Stability System Not Selected or Not Available</b>	0
<b>Single Drive Axle (Model 337)</b>	0

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	4/18/2018 10:34:35 AM	<b>Complete</b>	Model Number:	Model 337
Effective Date:	Jan 1, 2018		Quote/DTPO/CO:	Q83350335
Prepared by:	Tim Lopez		Version Number:	36.21



Description	Weight
<b>Anti-Lock Braking System (ABS) 4S4M</b> ABS-6. Includes air braking system.	0
<b>Bendix Air Cam Rear Drum Brakes 16.5x8.6</b> Includes Automatic Slack Adjusters & Outboard Mounted Brake Drums. Refer to TSB 11-57 for more information.	0
<b>Ratio 5.57 Rear Axle</b>	0
<b>Peterbilt Air Trac 20,000 lb Light Weight</b>	175
<b>Dash Mtd Dump Switch With Indicator Light</b> For suspension	2

**Engine & Equipment**

<b>PACCAR PX-7 300@2600 GOV@2600 660@1600</b> Performance (2017 Emissions) Includes alum flywheel housing, cruise control, and J1939 provisions (provides an interface point for the Electronic Service Analysis-ESA and other PACCAR approved diagnostic tools). Chevron Delo LE SAE 10W30 engine oil is specially formulated for new low emissions engines. Magnetic engine oil drain plug captures and holds any metal fragments in engine oil to extend service life. N21320 N205 120..Standard Maximum Speed Limit [LSL] N21330 N207 0....Expiration Distance N21340 P005 120..Hard Maximum Speed Limit N21350 P001 64...Maximum Accelerator Pedal Vehicle Speed N21360 P110 0....Accelerator Lower Droop N21370 P059 64...Maximum Cruise Speed N21380 P111 0....Cruise Control Lower Droop N21400 N203 252..Reserve Speed Function Reset Distance N21410 N202 0....Maximum Cycle Distance N21420 N206 10...Maximum Active Distance N21430 N201 0....Reserve Speed Limit Offset N21440 P015 NO...Engine Protection Shutdown N21450 P026 NO...Gear Down Protection N21460 P046 1400.Max PTO Speed N21470 P062 NO...Cruise Control Auto Resume N21480 P068 NO...Auto Engine Brake in Cruise N21500 N209 0....Expiration Distance N21510 P520 YES..Enable Idle Shutdown Park Brake Set N21520 P030 5....Timer Setting N21530 P233 YES..Enable Impending Shutdown Warning N21540 P234 60...Timer For Impending Shutdown Warning N21550 P516 35...Engine Load Threshold N21570 P031 NO...Idle Shutdown Manual Override N21590 P230 YES..Enable Hot Ambient Automatic Override N21610 P172 40...Low Ambient Temperature Threshold N21630 P171 80...High Ambient Temperature Threshold	-540
<b>Engine Idle Shutdown Timer Disabled</b>	0
<b>Eff EIST NA Expiration Miles</b>	0
<b>Effective VSL Setting NA</b>	0

**Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.**

Printed:	4/18/2018 10:34:35 AM	<b>Complete</b>	Model Number:	Model 337
Effective Date:	Jan 1, 2018		Quote/DTPO/CO:	Q83350335
Prepared by:	Tim Lopez		Version Number:	36.21



Description	Weight
<b>CARB Engine Idling Compliance</b> PACCAR PX-7, PX-9 and MX, Cummins ISL, ISM and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard.	0
<b>PACCAR 160 Amp Alternator, Brushed</b>	0
<b>PACCAR 12V Starter</b>	0
<b>2 Optima DT31T Batteries 1800 CCA Threaded</b> Stud type terminal. AGM (Absorbent Glass Material). Stranded copper battery cables are double aught (00) or larger to reduce resistance.	-4
<b>2-Speed Fan Clutch For Frequent Start/Stops</b>	0
<b>18.7 CFM Air Compressor</b> N/A X15. Furnished on engine. Teflon lined stainless steel braided compressor discharge line.	0
<b>VGT Exhaust Brake</b> (Variable Geometry Turbo). Provides approximately 90-100 HP of retardation and is part of the turbocharger.	0
<b>Spin-On Fuel/Water Separator</b>	0
<b>No Fluid Heat Option for Fuel Filter</b>	0
<b>No Electric Heat Option for Fuel Filter</b>	0
<b>Engine Protection Shutdown</b> Includes oil pressure, oil temperature, coolant temperature, and intake manifold temperature.	0
<b>High Efficiency Cooling System</b> Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. ClimaTech extended life coolant extends maintenance intervals which reduces maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 587: 1330 sq in, 579/367 FEPTO 1325 sq in, 567/365/367: 1440 sq in, 384/386: 1301 sq in, 365 FEPTO: 1184 sq in, 389/367 HH: 1669 sq in, 348: 1000 sq in, 320: 1242 sq in.	0
<b>Radial Seal, Dry Type Air Cleaner, Frontal</b> Air Intake. Molded rubber air intake connections with lined stainless steel clamps seal to prevent contaminants in air intake.	0
<b>Exhaust Single RH Horizontal</b> DPF/SCR RH Under Frame (2017).	-158

**Transmission & Equipment**

<b>Unpublished options may require review/approval.</b>			
<b>Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.</b>			
Printed:	4/18/2018 10:34:35 AM	<b>Complete</b>	Model Number: Model 337
Effective Date:	Jan 1, 2018		Quote/DTPO/CO: Q83350335
Prepared by:	Tim Lopez		Version Number: 36.21



Description	Weight
<b>Allison 2500 HS Transmission, Gen 5</b> Highway Series. Includes Allison Shift Performance, TranSynd Automatic Transmission Fluid, and Water Oil Heat Exchange. Also includes dash mounted indicator light when the transmission fluid, filter or clutches need service. (Meets the needs of on-highway vehicles that do not require PTO operation - the HS series provides no PTO provisions) Forward Ratios: 1st-3.51, 2nd-1.90, 3rd-1.44, 4th-1.00, 5th-0.74, 6th-0.64 / Reverse Ratios: DR-(5.09)	-170
<b>1710 HD Driveline, 2 Midship Bearings</b>	100
<b>Allison FuelSense Not Desired</b>	0
<b>Allison 6-Speed Configuration</b> Wide ratio gears. 2500 series transmissions.	0
<b>Dash Mounted Push Button Shifter</b> Available with Allison Transmissions.	0
<b>Air &amp; Trailer Equipment</b>	
<b>Bendix AD-IS Air Dryer W/Heater</b> And Coalescing Filter	0
<b>Pull Cords All Air Tanks</b>	0
<b>Nylon Chassis Hose</b>	0
<b>Steel Painted Air Tanks</b> All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	0
<b>Body Connections 5ft BOC</b> Junction Box contains light and power circuits for Body Connections located 5ft from BOC.	4
<b>Tires &amp; Wheels</b>	
<b>FF: BR 14ply 11R22.5 R268 Ecopia</b> Diameter = 41.5 inches; SLR = 19.3 inches	8
<b>RR: BR 16ply 11R22.5 M853</b> Diameter= 41.8 inches; SLR= 19.4 inches	92
<b>Code-rear Tire Qty 04</b>	0
<b>FF: Accu-Lite Steel Armor 51408PK 22.5X8.25</b> PHP10-2 hand holes	0
<b>RR: Alcoa 883677 22.5X8.25 Clean Buff Finish</b> Aluminum	-88
<b>Code-rear Rim Qty 04</b>	0

**Fuel Tanks**

**Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.**

Printed:	4/18/2018 10:34:35 AM	<b>Complete</b>	Model Number:	Model 337
Effective Date:	Jan 1, 2018		Quote/DTPO/CO:	Q83350335
Prepared by:	Tim Lopez		Version Number:	36.21



Description	Weight
<b>23in Aluminum 70 Gallon Fuel Tank RH U/C</b> Includes steps for cab access. Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	-117
<b>Location RH U/C 70 Gallon</b>	0
<b>Perforated Metal Anti-Siphon Device(s)</b> (Requires Engineering review with Arctic Fox or Split Fuel Tanks)	0
<b>DEF Tank Mounted LH BOC</b> Models 210, 220 and 320 mounted LH cab fender.	0
<b>Standard DEF To Fuel Ratio 2:1 Or Greater</b>	0
<b>DEF Tank Small</b>	0
<b>Battery Box &amp; Bumper</b>	
<b>Aluminum Battery Box LH Under Cab, Non-Slip Step</b> Includes diamond pattern block shaped cover in traditional/vocational models and a smooth finish tapered cover on aerodynamic models.	-55
<b>Rubber Battery Pad In Bottom Of (1) Battery Box</b> Mat in box that holds batteries only	2
<b>Steel Styled Aero Bumper Painted Black</b> 2 Tow pins	0
<b>Cab &amp; Equipment</b>	
<b>Alum Cab 108in BBC Metton Hood w/Bright Crown</b> Includes view window RH door and convex mirror over RH door.	0
<b>Thermal Insulation Package in Cab</b> Includes thick, closed-cell foam in floor, special mylar-faced foam in walls and roof structure.	2
<b>Peterbilt UltraRide Driver Seat</b>	0
<b>Peterbilt UltraRide Passenger Seat</b>	0
<b>Black Seat Color ipo Standard Color</b>	0
<b>Air Ride Driver</b>	0
<b>High Back Driver</b>	0
<b>Mordura Driver</b>	0
<b>Non-Air Ride Passenger</b>	0
<b>Low Back Passenger</b>	0
<b>Mordura Passenger</b>	0
<b>Adjustable Steering Column - Tilt/Telescope</b>	11
<b>Steering Wheel with Peterbilt Logo</b> Steering Wheel with embossed Peterbilt logo over horn button.	0

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	4/18/2018 10:34:35 AM	<b>Complete</b>	Model Number:	Model 337
Effective Date:	Jan 1, 2018		Quote/DTPO/CO:	Q83350335
Prepared by:	Tim Lopez		Version Number:	36.21



Description	Weight
<b>Interior Grey/Black</b> Includes rugged charcoal instrument panels, glare-resistant gray dash, black bezels on gauges, (2) power ports, monochromatic molded door pads with durable in-mold color, gray molded back wall, 18 inch 4-spoke soft-touch steering wheel, soft-touch steering column cover, power lift passenger window, extruded rubber floor covering, header-mounted dome light, foot well lighting, integrated "dead pedal", (4) inside entry grab handles, (2) inside sunvisors, (2) coat hooks, (2) cup holders and map bin in dash.	0
<b>Cab Rear Corner Windows - Standard Tint</b>	4
<b>Extended Rear Window ipo Std Window-Day Cab</b> The extended rear window protrudes two inches more than the standard conventional rear cab window. Take this into consideration when determining your loadspace.	0
<b>Day Cab Rear Window</b>	0
<b>One Piece Curved Windshield</b>	0
<b>Combo Fresh Air Heater/Air Conditioner</b> With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0
<b>Cup Holder (Floor Mounted)</b> Includes two standard-size drink holders and one extra-large jugholder, coin tray, and clipboard-size storage area.	4
<b>Outside Sunvisor - Stainless Steel</b> Not available with 2.1M high roof sleeper or furnished by owner sleeper.	4
<b>Mirrors SSTL Each Side Heated and Motorized</b> with Switch on Door. Right Click on option to See Picture in Product Portfolio.	2
<b>(2) Convex 8 Inch SS Mirrors</b> Center mounted under mirror bracket. If rear view mirrors are heated, the convex mirrors will be heated. Option includes dual door stops.	4
<b>Mirror Aux RH Fender/Hood</b> (2 legs on fender and 1 leg on hood)	4
<b>Mirror Aux LH Fender/Hood</b> (2 legs on fender and 1 leg on hood)	4
<b>Power Package</b> Includes power door locks and power windows.	0
<b>(1) Air Horn 24.5in Chrome - Round w/Horn Shield</b>	8
<b>No Head Unit or Audio Speakers Selected</b>	0
<b>CB Terminals/Wiring Mtd Under Header</b>	0
<b>Plug-In Auto Reset Circuit Breaker</b> in place of fuses in junction box.	0
<b>Peterbilt Electric Windshield Wipers</b> With Intermittent Feature.	0

Unpublished options may require review/approval.  
 Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	4/18/2018 10:34:35 AM	<b>Complete</b>	Model Number:	Model 337
Effective Date:	Jan 1, 2018		Quote/DTPO/CO:	Q83350335
Prepared by:	Tim Lopez		Version Number:	36.21



Description	Weight
<b>CabMate Cab Air Suspension</b> Mfg by Link. The class 8 conventionals (except Model 348) includes (2) airbags, (2) shock absorbers, (1) leveling valve, radius rod, and height limiter. The Models 330, 337, and 348 includes (1) airbag and (1) shock absorber.	15
<b>Triangle Reflector Kit Shipped Loose</b>	13
<b>Fire Extinguisher; Cab Mounted</b> Hazmat approved UL listed/rated ABC.	8
<b>Backup Alarm (107dB)</b>	3
<b>Main Transmission Oil Temperature Gauge</b> Located in Driver Information Display	0
<b>Air Restriction Indicator</b> Mounted on air cleaner, intake piping, or firewall.	0
<b>Bright Bezel Gauges</b>	0
<b>(2) Additional Electric Switches Without Wiring</b>	0
<b>Main Instrumentation Panel, Graphics Display</b> Includes speedometer with trip odometer, tachometer with hourmeter and outside air temperature display, voltmeter, engine oil pressure, engine coolant temperature, fuel level, primary and secondary air pressure gauges. Includes standard warning light package: high water temperature, low oil pressure, and low air pressure warning lights w/audible alarms, high beam, turn signal, low fuel, parking brake, and ice warning indicators; seat belt reminder; rocker switches with long-life LED indicators; multi-function turn stalk with flash-to-pass feature (night mode flashes headlights and marker lights; day mode flashes headlights only), intermittent windshield wiper and headlamp beam control. Hydraulic braked trucks do not include air pressure gauges.	0
<b>Headlights Composite Fender Mounted</b> Integral park, turn, and side marker	0
<b>(5) Marker Lights, Aero LED</b> Light Emitting Diodes	0
<b>(2) Peterbilt Fog Lights</b> Recessed in bumper	6
<b>None Furnished Stop/Tail/Backup Lights</b> Available with Full Truck only. Not available with Tractor.	0
<b>Paint</b>	
<b>Standard Paint Color Selection</b>	0
<b>(1) Color Axalta Two Stage - Cab/Hood</b>	0
Base Coat/Clear Coat	
N85020 A - L0006EY WHITE	
N85400 HOOD TOP L0006EY WHITE	
N85500 CAB ROOF L0006EY WHITE	
N85200 FRAME N0001EA BLACK	
N85700 BUMPER N0001EA BLACK	
N85300 FENDER L0006EY WHITE	

\* Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	4/18/2018 10:34:35 AM	<b>Complete</b>	Model Number:	Model 337
Effective Date:	Jan 1, 2018		Quote/DTPO/CO:	Q83350335
Prepared by:	Tim Lopez		Version Number:	36.21



	Description	Weight
<b>Shipping Destination</b>		
	<b>Shipping Destination Other Than Dealer</b> (Specify by narrative) N89900 1 N89910 1 N89920 1, 1 1 N89930 1 1	0
<b>Options Not Subject To Discount</b>		
	<b>Peterbilt Class 7 Standard Coverage</b> 1 year/Unlimited Miles/km	0
	<b>PACCAR PX-7 Standard Coverage</b> 3 years/Unlimited Miles/Unlimited hrs	0
	<b>Paccar 2017 PX-7 Protection Plan 1 (6/150)</b> Six Years/150,000 Miles/241,402 Kilometers. Coverage is 100 percent parts and labor with no deductibles on internally lubricated components and major engine systems including turbo charger, water pump, and fuel injectors.	0
	<b>Paccar 2017 PX-7 Aftertreatment Coverage</b> 6 Yrs/150K Mi (241,402 KM)	0
<b>Miscellaneous</b>		
	<b>2017 EPA Emissions Engine</b> Warranty Only Marathon Truck Bodies 25655 Springbrook Ave Santa Clarita Ca. 91350 Phone: 661-286-1520	0
	<b>Presentation Created Using Featured Spec</b> For Model	0
<b>Promotions</b>		
	<b>PacLease Medium Duty 2006</b>	0
<b>Total Weight</b>		10103

**Prices and Specifications Subject to Change Without Notice.**

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	4/18/2018 10:34:35 AM	<b>Complete</b>	Model Number:	Model 337
Effective Date:	Jan 1, 2018		Quote/DTPO/CO:	Q83350335
Prepared by:	Tim Lopez		Version Number:	36.21